

## Basic parameters

Dimensions (W x H x D)	6.3 x 6.9 x 0.4 inches / 161 x 174 x 11 mm
Weight (including stand)	0.6 lbs / 280 g
Main bodycolor	Gray
Power supply	Via USB, no additional power adapter required
Power consumption	1.0 W maximum
Communication interface	USB

## LCD Display

DisplayType	F-STN
Cover plate surface	Tempered glass
Native resolution	320 x 200 pixels

## Pad and Pen

ReadingTechnology	Electromagenetic Resonance (EMR)
Active area size	3.8x 2.4 inches / 96 x 60 mm
Coordinate resolution	2540 lpi / 0.01 mm/pt (non-interpolated)
Coordinate accuracy	±0.02 inches / ±0.5 mm (center)
Report rate	200 points per second (non-interpolated)
Pressure levels	1024 (non-interpolated)
Encryption	AES256 / RSA2048

## Miscellaneous

Pen storage	Pen tray
Connectivity security	USB cable locking system
Data security	Real time signature capture without internal pad memory
Securitylock slot	Yes, Kensington
Operating temperature, relative humidity	+41° F to +104° F (+5° C to +40° C),(humidity30 % to 80 % RH, no condensing)
Storage temperature, relative humidity	-4° F to +140° F (-20° C to +60° C), (humidity30% to 90% RH, no condensing)
Signature software compatability	Compatible with Windows signature / eSign software and Wacom's sign pro PDF and sign pro PDF Plug-in for Adobe Acrobat. For Windows, C++, .Net and Java development libraries available for developers (contact us for libraryand software availabilityin other development languages and platforms)
Package content	Signature pad, cordless and battery-free pen, USB cable (9.84 ft / 3 m), quick start guide, pen tether (nylon fber, 19.7inch / 50 cm)